
# HOW TO MAKE A STRENGTHENING RIDGE IN A BUCKET

One or two ridges around the rim of a bucket will increase its strength and make it more ridged making it easier to use. One method of making ridges is with a wooden stake and mallet. Another method is to use a spring jenny. Ridges can be added to other metal objects to make them stronger.




Use a saw to cut grooves in a straight round hard log. Make two cuts, the width of the groove apart, straight across the log. Remove the wood between the cuts with a knife. The distance between the grooves will be the distance between the ridges made in the bucket.


Drill (or burn with hot steel rod) two pairs of holes in the bench.

Use strong wire to fix the log to the bench, positioning the log so that the grooves are the distance from the bench edge that you wish the ridges to be from the rim of the bucket

















## Making the ridge

- 1) Place the bucket over the log so the metal lies flat along the log, and the rim presses against the edge of the bench.
- 2) Make a wedge-shaped hardwood mallet, and strike the metal above a groove, forcing the metal down into the groove. Turn the bucket slowly round as the ridge forms.
- Make the other ridge with the second aroove.

Practical Action, The Schumacher Centre for Technology & Development
Bourton Hall, Bourton-on-Dunsmore, Rugby, Warwickshire CV23 9QZ, UK
Tel: +44 (0)1926 634400 Fax: +44 (0)1926 634401 E-mail: infoserv@practicalaction.org.uk Web: www.practicalaction.org

Strengthening ridges **Practical Action** 


# Making a ridge with a spring jenny



'Female' tool made by fixing two lengths of steel rod straight across, apart so that the 'male' tool just fits between the two steel rods when pushed down.

### Making the ridge

- 1) Place guide pegs in equal holes, to quide where the ridge will be made.
- 2) Place rim of the bucket against guide oegs, so that the outside of the bucket presses down against the female tool, so the male tool is on the inside of the bucket.
- 3) Strike the top of the male tool repeatedly with a hammer or mallet, and rotate the bucket slowly as the ridge is formed,
  - taking care that the bucket rim always rests against the guide pegs.
- 4) When ridge is completed, move guide pegs and repeat the process for another ridge.



- How to Make a Folding Machine for Sheet Metal Work Workshop Equipment 1 Rob Hithings, ITDG Publishing
- How to Make a Foot-operated Workshop Drill Workshop Equipment 2 Paul Smith, ITDG Publishing
- How to Make a Rolling Machine for Sheet Metal Work Workshop Equipment 3 Rob Hitchings, ITDG Publishing
- How to Make Cutting Shears for Sheet Metal Workshop Equipment 4 Rob Hutchings, ITDG Publishing
- How to Make a Hand-operated Holepunch Workshop Equipment 7 Ted Stone and Jim Tanburn
- How to make a Metal-bending Machine Workshop Equipment 10 R.D. Mann, ITDG Publishing





Filename: 9B5763AF

Directory: C:\Documents and Settings\neilnob\Local Settings\Temporary

Internet Files\Content.MSO

Template: C:\Documents and Settings\neilnob\Application

Data\Microsoft\Templates\Normal.dot

Title: How to make a ridge in a Bucket Using a Stake and Mallet

Subject:

Author: Practical Action

Keywords:

Comments: Adapted in September 2003 by Neil Noble

Creation Date: 9/4/2003 4:36:00 PM

Change Number: 16

Last Saved On: 9/23/2005 4:25:00 PM

Last Saved By: Neil Noble
Total Editing Time: 124 Minutes

Last Printed On: 4/22/2008 11:44:00 AM

As of Last Complete Printing Number of Pages: 2

Number of Words: 317 (approx.)

Number of Characters: 1,812 (approx.)